METHOD AND APPARATUS FOR IMPLEMENTING MULTIPLE DIAL PADS ON A PORTABLE ELECTRONIC DEVICE

RESERVATION OF COPYRIGHT

[0001] A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by any one of the patent document or patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyrights whatsoever

FIELD OF THE INVENTION

[0002] Embodiments relate generally to the implementation of multiple dial pads on a portable electronic device and related methods and apparatuses disclosed herein.

BACKGROUND OF THE INVENTION

[0003] Portable electronic devices such as mobile telephones or personal digital assistants (PDAs) generally include a keypad for user input. Traditionally, the keypad is a set of physical keys or buttons that a user may push in order to make user selections. For instance, a cellular telephone may include a grid of physical keys or buttons that may be pushed in order to dial a phone number. However, in more recent portable electronic devices, the keypad is implemented as a virtual keypad displayed on a touch screen. The touch screen of the portable electronic device displays regions that may be touched by a user. The regions may be associated with digits 0-9, although other associations are possible (e.g., *, #, etc.). Selection of a region by a user results in the dialing of the corresponding digit in a phone number. The regions act as buttons or keys and generate a signal when touched. The signals generated are interpreted by the portable electronic device and result in the dialing of a phone number defined by the numbers associated with the touched regions.

[0004] Generally, a touch screen of a portable electronic device displays the virtual push button dial pad when the device is in a phone number dialing mode. In this mode, not only does the device display a dialing key pad, but the device also interprets user input through the dialing keypad in order to assemble and dial phone numbers. When the device is not in a phone number dialing mode, the virtual dial pad is not displayed and user input does not automatically result in the dialing of a phone number.

[0005] In many cases, the virtual dial pad displayed on a portable electronic device touch screen is similar in orientation and function to a standard touch tone telephone dialing pad. That is, the numbered buttons are arranged in four rows of keys, three columns wide. Numbers 0-9 are represented on the virtual "keys." A "star" ("*") key and a "pound" ("#") key are usually also displayed. Other alpha-numeric symbols may also be associated with the virtual keys. Using this standard orientation, a user may dial a phone number by pushing the appropriate virtual keys. Thus, a user may dial a phone number using a touch screen of the portable electronic device in a way that is similar to most other touch tone dial pads function.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates a portable electronic device for communicating with a network in accordance with an embodiment disclosed herein.

[0007] FIG. 2 illustrates the internal components of the portable electronic device in accordance with an embodiment disclosed herein.

[0008] FIG. 3 illustrates a conventional dial pad configuration on a portable electronic device.

[0009] FIGS. 4A and 4B illustrate dial pad configurations in accordance with an embodiment disclosed herein.

[0010] FIG. 5 illustrates a dial pad configuration in accordance with an embodiment disclosed herein.

[0011] FIG. 6 illustrates a dialing configuration in accordance with an embodiment disclosed herein.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Example embodiments and applications will now be described. It should be appreciated that other embodiments may be realized and structural or logical changes may be made to the disclosed embodiments.

[0013] An advantage of using a touch screen to display a virtual dial pad is that the dial pad need not be limited to a specific orientation such as the standard dial pad orientation. Because there is a desire, and even a need, for additional virtual dial pads to be used on a portable electronic device with a touch screen, embodiments of multiple virtual dial pads integrated into the portable electronic device are disclosed below.

[0014] FIG. 1 illustrates a portable electronic device 210 according to a disclosed embodiment. The portable electronic device 210 is a dual mode (simultaneous data and voice communication capabilities) device, personal digital assistant, etc. Such devices include BlackBerryTM devices by Research in Motion Limited of Ontario, Canada, or Palm® Treo™ devices by Palm, Inc. of California, U.S.A. to name a few. In addition, the portable electronic device 210 may be a cellular telephone. The device 210 includes a portable housing 212 and a touch screen display 214 such as a capacitive or resistive touch screen display. The device 210 may also include a physical keyboard, though, as explained below, a physical keyboard can be replaced by a virtual keyboard on the touch screen display 214. The device 210 may include additional physical buttons such as a menu button 216, a go back button 217, a dial button 218 and an end call button 219. The menu button 216, when pushed, results in the display of a menu on the touch screen display 214. The go back button 217 allows a user to go back to a previously viewed image or page on the display 214. The dial button 218 and end call button 219, as explained in more detail below, are used to begin and end phone calls. The device 210 also includes a plurality of additional physical buttons 222 that may be used to activate certain default applications or features of the device 210 when pushed, or which may be customizable to perform desired functions when pushed. The touch screen display 214 displays menus and applications that may be selected by a user through touching the appropriate region of the touch screen display 214.

[0015] The device 210 also includes internal components that may be implemented through a combination of both hardware and software. Internal components 800 of the device 210 are illustrated in FIG. 2. The portable electronic device 210 includes a number of components such as a main processor 802 that controls the overall operation of the portable electronic device 210. Communication functions, including data and voice communications, are performed through a communication subsystem 804. The communication subsystem 804 receives messages from and sends mes-